

# Actifio™ 100T Specifications

## Specifications Summary

<b>Host Interface</b>	1 Gbps/10Gbps/FC
<b>User Interface</b>	<ul style="list-style-type: none"> <li>• Actifio Graphical User Interface</li> <li>• Command Line Interface</li> </ul>
<b>Software</b>	Software Actifio 5.x software
<b>Appliance</b>	<ul style="list-style-type: none"> <li>• Fully redundant servers with battery backed cache</li> <li>• Dual controller SAN storage</li> </ul>
<b>License and capacity</b>	Ranges from 15TB to 100TB application data protection
<b>Warranty</b>	<ul style="list-style-type: none"> <li>• 3-year limited warranty</li> <li>• Customer-replaceable units</li> <li>• On-site service</li> <li>• Next business day replacements</li> <li>• Free software maintenance upgrades</li> </ul>
<b>Size</b>	<p><b>Approximate Weight:</b></p> <p>Between 366-1252Lbs depending on the configuration</p>
<b>Operating Environment</b>	<p><b>Electrical Power:</b></p> <ul style="list-style-type: none"> <li>• Voltage Range: 100 – 240V AC</li> <li>• Frequency: 50 – 60 Hz</li> </ul> <p><b>Maximum Power for 115v based systems</b></p> <ul style="list-style-type: none"> <li>• 12.1 AMPs – 39.5 AMPs depending on configuration</li> <li>• 1391 – 4537 Watts depending on configuration</li> </ul>
<b>Heat Dissipation (BTU per hour)</b>	5103 BTU/hr – 16200 BTU/hr depending on the configuration
<b>Supported Systems</b>	See the interoperability support matrix

CONFIG	MANAGED CAPACITY (TB)	VOLTAGE (V)	AMPS (A) (MAX)	WATTS (VA) (MAX)	BTU/HR (MAX)	WEIGHT (LBS) (MAX)	WEIGHT (KG) (MAX)	RACKSPACE (U)
100T-15	15	115	12.1	1391	5103	366	166	12
100T-30	30	115	15.5	1781	6435	481	218	16
100T-45	45	115	18.9	2171	7767	597	271	20
100T-60	60	115	29.3	3367	12204	904	410	30
100T-75	75	115	32.7	3757	13536	1020	463	34
100T-90	90	115	36.1	4147	14868	1136	515	38
100T-100	100	115	39.5	4537	16200	1252	568	42
100T-ROBO	10	115	8.2	944	3494	400	181	15

## Supported Protected Operating Environments

### Fully Automated Application Integration

- VMware ESX 4.x, 5.x
- Microsoft® Windows 2000, 2003 and 2008
- Microsoft® SQL Server 2005, 2008, and 2012
- Microsoft® Exchange 2007, 2010 and 2013
- Microsoft® Exchange DAG
- Microsoft® Sharepoint 2007, 2010 and 2013
- Red Hat Enterprise Linux®, Advanced Server 5.x, 6.x
- SAP BRTools
- SUSE Linux Enterprise Server 11
- Oracle 10g, 11g

### Application and OS Integration via Command Line

- Novell NetWare V6.5
- Sun Solaris 8, 9, 10
- IBM AIX V4.3.3
- IBM AIX 5LTM V5.1, V5.2, V5.3
- IBM AIX V6.1
- IBM DB2
- IBM iSeries
- IBM z/VSE V4.2
- IBM PowerVM Virtual I/O Server 1.2, 1.3, 1.4, 1.5
- HP-UX 11.0, 11i V1, V2, V3
- Red Hat Enterprise Linux®, Advanced Server 2.1, 3.0, 4.0, 5.0
- SUSE Linux Enterprise Server 8, 9, 10
- HP Tru64 5.1A, 5.1B
- HP OpenVMS 7.3-2, 8.2, 8.3
- SGI Irix 6.5.28, Altix SLES 9
- IBM N series Gateways
- NetApp V-Series
- ONStor Clustered NAS Gateway

### Storage Systems Support

- Specific models of the following storage systems:
- Compellent SC800
  - EMC Symmetrix DMX and 8000-series models
  - EMC CLARiiON CX-series models and FC4700
  - IBM Storwize V3700
  - IBM Storwize V7000
  - IBM TotalStorage Enterprise Storage Server®, IBM System Storage DS3000, DS4000TM, DS5000, DS6000TM, DS8000, N series
  - IBM XIV® Storage System
  - Hitachi Data Systems HUS
  - Hitachi Data Systems Thunder, Lightning, TagmaStore, AMS, WMS, Universal Storage Platform
  - Huawei storage
  - Sun StorEdge systems, Sun StorageTek systems, FlexLine 200
  - Hewlett Packard MA8000, EMA12000, EMA16000, EVA family, MSA family, XP family, 3PAR
  - NetApp FAS
  - Bull StoreWay
  - Fujitsu Eternus
  - NEC iStorage
  - Nexsan storage
  - Pillar Axiom
  - Storage virtualized behind IBM SVC
  - LSI Engenio 2600
  - Violin Memory

### Host Multipathing Software

- IBM System Storage Multipath Subsystem Device Driver (SDD)
- Symantec/Veritas Volume Manager 3.5 MP3, 4.0, 4.1, 4.3, 5.0
- PVLinks for HP-UX
- MPIIO for Windows® and IBM AIX®
- MPxIO for Solaris
- Native NetWare multipathing driver
- Native VMware multipathing driver for VMware ESX 4.X and later
- Native multipathing drivers for OpenVMS, Tru64, SGI Irix

### Support for SAN switches—Selected Models from the Following Suppliers

- Brocade
- McDATA
- Cisco
- CNT

For more information on how Actifio can manage data simply, visit [www.actifio.com](http://www.actifio.com).

**actifio**  
Radically Simple



©Actifio, Inc. All rights reserved. Actifio™ is a registered trademark of the Actifio Corporation. All other trademarks and service marks are property of their respective owners